

AF - CE

Mod Cod PPRE P_{MAX}

: -10° ÷ +99°C

Mod	Cod		PPRE	P _{MAX}							
AF 35 CE	A032L31	35	1,5	10	+99°C	400	-	400	3/4" - 1"	-	410 x 410 x 410
AFH 50 CE	A042L34	50	1,5	10	+99°C	400	425	515	1"	-	410 x 530 x 440
AFV 50 CE	A032L34	50	1,5	10	+99°C	400	600	-	1"	-	410 x 410 x 610
AFH 60 CE	A042L35	60	1,5	10	+99°C	400	480	675	1"	1/2" F 3/4" M	410 x 685 x 490
AFV 60 CE	A032L35	60	1,5	10	+99°C	400	750	-	1"	1/2" F 3/4" M	410 x 410 x 760
AFH 80 CE	A042L37	80	1,5	10	+99°C	400	480	765	1"	1/2" F 3/4" M	410 x 775 x 490
AFV 80 CE	A032L37	80	1,5	10	+99°C	400	815	-	1"	1/2" F 3/4" M	410 x 410 x 860
AFH 100 CE	A042L38	100	1,5	10	+99°C	500	585	720	1"	1/2" F 3/4" M	510 x 730 x 600
AFV 100 CE	A032L38	100	1,5	10	+99°C	500	805	-	1"	1/2" F 3/4" M	510 x 510 x 830
AFV 100 CE	A032R38	100	1,5	16	+99°C	500	805	-	1"	1/2" F 3/4" M	510 x 510 x 830
AFV 150 CE	A032L43	150	1,5	10	+99°C	500	1030	-	1" 1/4	1/2" F 3/4" M	510 x 510 x 1040
AFH 200 CE	A042L47	200	1,5	10	+99°C	600	665	970	1" 1/4	1/2" F 3/4" M	610 x 950 x 680
AFV 200 CE	A032L47	200	1,5	10	+99°C	600	1065	-	1" 1/4	1/2" F 3/4" M	610 x 610 x 1110
AFV 200 CE	A032R47	200	1,5	16	+99°C	600	1065	-	1" 1/4	1/2" F 3/4" M	610 x 610 x 1110
AFH 300 CE	A042L51	300	1,5	10	+99°C	650	705	1130	1" 1/4	1/2" F 3/4" M	660 x 1140 x 720
AFV 300 CE	A032L51	300	1,5	10	+99°C	650	1270	-	1" 1/4	1/2" F 3/4" M	660 x 660 x 1290
AFV 300 CE	A032R51	300	1,5	16	+99°C	650	1270	-	1" 1/4	1/2" F 3/4" M	660 x 660 x 1290
AFV 500 CE	A032L55	500	1,5	10	+99°C	775	1420	-	1" 1/4	1/2" F 3/4" M	785 x 785 x 1440

